

M. ŁAŃCUCHY DO REDLERA • REDLER CHAINS

Nr kat. Cat. No.	Symbol ISO	Podziałka p Pitch p mm							b ₁ mm min	b ₂ mm max	d ₁ mm max	d ₂ mm	F mm	g mm	h mm	s mm	F _B kN min
		63	80	100	125	160	200	250									
M-1	MRC 56	63	80	100	125	160	200	250	24	33	10,0	15	*	30	20	4,0	56
M-2	MRC 80	80	100	125	160	200	250	315	28	39	12,0	18	*	35	25	5,0	80
M-3	MRC 112	80	100	125	160	200	250	315	32	45	15,0	21	*	40	35	6,0	112
M-4	MRC 160	100	125	160	200	250	315	—	37	52	18,0	25	*	50	40	7,0	160
M-5	MRC 224	125	160	200	250	315	400	—	43	60	21,0	30	*	60	44	8,0	224
M-6	MRC 315	160	200	250	315	400	—	—	48	70	25,0	36	*	70	50	10,0	315
M-7	CR42	80	100	125	—	—	—	—	18	24	10	15	*	25	20	3,0	42
M-8	CR64	100	125	160	—	—	—	—	22	30	12	18	*	30	25	4,0	64
M-9	CR100	100	125	160	—	—	—	—	25	35	14	20	*	35	30	5,0	100
M-10	CR120	100	125	160	—	—	—	—	30	42	16	22	*	40	35	6,0	120
M-11	CR145	125	160	200	—	—	—	—	35	47	18	26	*	45	38	6,0	145
M-12	CR190	125	160	200	—	—	—	—	45	61	20	30	*	50	44	8,0	190
M-13	CR275	160	200	250	—	—	—	—	55	71	26	36	*	60	50	8,0	275

* - Wymiar wg potrzeb klienta • Free Dimension

F_B - Obciążenie zrywające • Breaking Load