

N. ŁAŃCUCHY OGNIWOWE ZE STALI NIERDZEWNEJ K/O
• STAINLESS STEEL LINK CHAINS

Wg DIN 766/PN-M/84540 Krótkie ogniwa / Short Link					Wg DIN 763/PN-M/84543 Długie ogniwa / Long Link				
Nr kat. Cat. No.	d mm	t mm	b mm	Obciąż użytk. Working Load	Nr kat. Cat. No.	d mm	t mm	b mm	Obciąż użytk. Working Load
N-1	2,0	12,0	8,0	—	N-1 7	1,5	20,0	6,0	—
N-2	3,0	16,0	11,0	100,0	N-18	2,0	22,0	8,0	—
N-3	4,0	16,0	14,0	150,0	N-1 9	2,5	24,0	10,0	—
N-4	5,0	18,5	17,0	250,0	N-20	3,0	26,0	12,0	100,0
N-5	6,0	18,5	20,0	350,0	N-21	4,0	32,0	16,0	120,0
N-6	7,0	22,0	23,0	450,0	N-22	5,0	36,0	20,0	160,0
N-7	8,0	24,0	26,0	630,0	N-23	6,0	42,0	24,0	200,0
N-8	9,0	27,0	31,0	800,0	N-24	7,0	48,0	28,0	320,0
N-9	10,0	28,0	34,0	1000,0	N-25	8,0	54,0	32,0	400,0
N-10	11,0	31,0	36,0	1120,0	N-26	10,0	65,0	40,0	630,0
N-11	12,0	32,0	40,0	1440,0	N-27	12,0	82,0	48,0	750,0
N-1 2	13,0	36,0	44,0	1600,0	N-28	13,0	82,0	50,0	1000,0
N-1 3	14,0	42,0	48,5	1950,0	N-29	14,0	80,0	52,0	1250,0
N-1 4	16,0	45,0	54,0	2500,0	N-30	16,0	80,0	57,0	6250,0
N-1 5	18,0	50,0	60,0	3150,0	N-31	18,0	90,0	65,0	9000,0
N-1 6	20,0	56,0	67,0	4000,0	—	—	—	—	—