

S. ŁAŃCUCHY POCIĄGOWE TYP FV/DIN 8165 • CONVEYOR CHAINS DIN 8167 TYPE FV/DIN 8165

Nr kat. Cat. No.	Symbol ISO	Podziałka p Pitch p mm								b ₁ mm min.	d ₁ mm max.	d ₂ mm B	d ₃ mm S	d ₄ mm P	d ₅ mm F	d ₆ mm F	x mm	l ₁ mm	g mm	s mm	F _B kN min.
		40	50	63	80	100	125	160	—												
S-1	FV40	40	50	63	80	100	125	160	—	18	10	15	20	32	40	48	12,5	37	26	3	40
S-2	FV63	50	63	80	100	125	160	200	—	22	12	18	26	40	50	60	15,5	46	30	4	63
S-3	FV90	50	63	80	100	125	160	200	250	25	14	20	30	48	63	73	18,5	53	35	5	90
S-4	FV112	80	100	125	160	200	250	315	—	30	16	22	32	55	72	87	22,0	63	40	6	112
S-5	FV140	80	100	125	160	200	250	315	400	35	18	26	36	60	80	95	26,0	68	45	6	140
S-6	FV180	100	125	160	200	250	315	400	500	45	20	30	42	70	100	120	35,0	86	50	8	180

F_B - Obciążenie zrywające • Breaking Load