

L. ŁAŃCUCHY POCIĄGOWE WG NORMY: PN-M/84168/ DIN 8167 - TYP "MT" • CONVEYOR CHAINS DIN 8167 TYPE "MT"

Nr kat. Cat. No.	Symbol ISO	Podziałka p Pitch p mm							b ₁ mm min	d ₁ mm max	d ₂ mm B	d ₄ mm P	g ₁ mm	g ₂ mm	s mm	h mm	l ₂ mm	F _B kN min
		40	50	63	80	100	125	160										
L-1	MT20	40	50	63	80	100	125	160	16	6,0	9,0	25	25	16,0	3,0	33	37	20
L-2	MT28	50	63	80	100	125	160	200	18	7,0	10,0	30	30	20,0	3,0	36	40	28
L-3	MT40	63	80	100	125	160	200	250	20	8,5	12,5	36	35	22,5	3,5	41	45	40
L-4	MT56	63	80	100	125	160	200	250	24	10,0	15,0	42	45	30,0	4,0	48	54	56
L-5	MT80	80	100	125	160	200	250	315	28	12,0	18,0	50	50	32,5	5,0	55	64	80
L-6	MT112	80	100	125	160	200	250	315	32	15,0	21,0	60	60	40,0	6,0	65	73	112
L-7	MT160	100	125	160	200	250	315	-	37	18,0	25,0	70	70	45,0	7,0	75	85	160
L-8	MT224	125	160	200	250	315	400	-	43	21,0	30,0	85	90	60,0	8,0	85	97	224
L-9	MT315	160	200	250	315	400	-	-	48	25,0	36,0	100	100	65,0	10,0	100	114	315

F_B - Obciążenie zrywające • Breaking Load